

8 Channels Ultrasonic Multiplexer MUX-8



BRIEF TECHNICAL SPECIFICATION

No of Channel	:	8 separate channel with individual adjustment of delay and gain control.
Display	:	LCD Display 16 * 2 Alphanumeric for indication of parameter value.
Gain	:	Adjustment from -10dB to 30dB in step of 1db increment for each channel.
Delay	:	Adjustment from 0 to 99mm in step of 1mm increment for each channel.
Memory	:	10 calibration set-up can be store/recall.
Operating Mode	:	Factory set T+R / T-R internally selected.
Channel Status Indication	:	8 LED's for indication of on/off status of channel.
Keyboard	:	Sealed membrane keyboard with direct access key for channel selection.
Battery	:	Li-Ion battery pack 14.4VDC, 4Ah, gives 8 hours continuous operation from fully charged battery. Full charging is done within 4.5 hours.
Operating temperature	:	0 to 55 C.
Dimensions	:	152 x 255 x 70(HxWxD).
Weight	:	1.8 KG.

(Modification rights reserved, Color scheme may be change)

Manufactured and Marketed by

MODSONIC INSTRUMENTS MFG. CO.(P) LTD.

Plot No.33, Phase III, GIDC Industrial Estate, Naroda, Ahmedabad 382330 INDIA.

Tel : +91 (079) 2281 1217,2281 3131,2284 1294 Fax : + 91 (079)2282 0012

Email : modsonic@modsonic.com. Web site : www.modsonic.com

REPRESENTATIVES AT

Bangalore,Bhopal,Chennai, Hyderabad,Kolkata,Mumbai,Nagpur,New Delhi,Pune.